

ASB200-895 Slim Type System for IBASE IB895 3.5" Disk-Size SBC



Features

- Fanless system for IBASE IB895 3.5-inch Disk-Size SBC
- Onboard Intel® Atom™ Processor D2550, 1.86 GHz
- iSMART - auto-scheduler and power resume
- EuP/ErP power saving
- One 2.5" SATA storage device
- Available in black coating color
- Wall mount kit included
- 12V ~24V DC wide range power input

Specifications

| | |
|--------------------------|--|
| System Mainboard | IB895 / IB895N |
| CPU Type | Intel® Atom™ Processor D2550 / N2600 |
| System Speed | 1.86GHz / 1.6GHz |
| Memory | 1x DDR3 SO-DIMM, Max. 4GB (Intel® Atom™ D2550) 1x DDR3 SO-DIMM, Max. 2GB (Intel® Atom™ N2600) |
| Construction | Aluminum & Steel |
| Chassis Color | Black |
| Front Panel External I/O | Power LED, HDD LED, Reset button, On/Off button, Mic-in, Line-out, 4x USB ports, 3x COM ports |
| Rear Panel External I/O | 1x DVI-I, 2x USB ports, 1x COM, 2x RJ-45 connector, DC-in jack |
| Storage | 1x 2.5" HDD or SSD |
| Power Supply | 60W power adaptor |
| Mounting | Desktop or wall mount(wall mount kit included) |
| Dimensions | 240mm(W) x 162mm(D) x 37mm(H) |
| Operating Temperature | 0°C ~ 45°C (32°F ~ 113°F) |
| Storage Temperature | -20°C ~ 80°C (-4°F ~ 176°F) |
| Relative Humidity | 5~90% @ 45°C, (non-condensing) |
| Vibration | CFD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation |
| Certification | CE, FCC |

Ordering Information

| | |
|-------------|---|
| ASB200-895 | Fanless Chassis for IB895 3.5-inch Disk Size SBC, Intel® Atom™ D2550 (1.86GHz) CPU, 2.5" 320GB SATA HDD, 2GB DDR3 memory, 60W power adaptor |
| ASB200-895N | Fanless Chassis for IB895 3.5-inch Disk Size SBC, Intel® Atom™ N2600 (1.6GHz) CPU, 2.5" 320GB SATA HDD, 2GB DDR3 memory, 60W power adaptor |

Dimensions and Drawing

