

System	PT-108PF	PT-100PF
Motherboard Type	Intel	Intel
Form Factor	3.5" EBC	3.5" EBC
System Chipset	Intel 852GM+ICH4	Intel 852GM+ICH4
CPU Supporting	Intel ULV 1GHz(non L2 Cache)	Intel ULV 1GHz(non L2 Cache)
FSB	400MHz	400MHz
DIMM Socket	One 200-PIN SO-DIMM DDR266 up to 1GB Default 512MB	One 200-PIN SO-DIMM DDR266 up to 1GB Default 512MB
Graphic	Integrated Intel 852GM GMCH	Integrated Intel 852GM GMCH
Audio	VIA VT1618 AC'97 Codec	VIA VT1618 AC'97 Codec
LAN Controller	10/100/1000 Mbps, VIA VT6122 LAN, support PXE RJ-45 *1	10/100/1000 Mbps, VIA VT6122 LAN, support PXE RJ-45 *1
I/O Connector	Serial port *3 USB port *2 PS/2 Mini DIN Keyboard Port & Mouse Port Audio Line in/out and Mic in Jacks VGA port *1	Serial port *3 USB port *4 PS/2 Mini DIN Keyboard Port & Mouse Port Audio Line in/out and Mic in Jacks VGA port *1
Display		
Size	8.4" TFT LCD	10.4" TFT LCD
Contrast Ratio	150 : 1	220 : 1
Brightness	250cd/m ²	250cd/m ²
Resolution	800 * 600	800 * 600
Mechanical		
Touch	Default Taiwan 5wire resistive touch or ELO by option	Default Taiwan 5wire resistive touch or ELO by option
Device	2.5" IDE HDD * 1 (Support Ultra DMA-66/100), default 40GB	2.5" IDE HDD * 1 (Support Ultra DMA-66/100), default 40GB
Power Supply	60W ATX power adapter	60W ATX power adapter
Bezel	Plastic black color front bezel	Plastic black color front bezel
Dimension	220 * 192 * 56	276 * 218.5 * 56
Optimal Ordering	1~3 track MSR WiFi (Mini-PCI) with Antenna	1~3 track MSR WiFi (Mini-PCI) with Antenna


System	PT-120PF	PT-150PF	PT-170PF
Motherboard Type	Intel	Intel	Intel
Form Factor	Mini-ITX	Mini-ITX	Mini-ITX
System Chipset	Intel 852GM/Intel ICH4	Intel 852GM/Intel ICH4	Intel 852GM/Intel ICH4
CPU Supporting	Intel ULV 1GHz(non L2 Cache)	Intel ULV 1GHz(non L2 Cache)	Intel ULV 1GHz(non L2 Cache)
FSB	400MHz	400MHz	400MHz
DIMM Socket	One 184 PIN DIMM DDR266 SDRAM Up to 1GB, default 512MB	One 184 PIN DIMM DDR266 SDRAM Up to 1GB, default 512MB	One 184 PIN DIMM DDR266 SDRAM Up to 1GB, default 512MB
Graphic	Integrated Intel 852GM GMCH	Integrated Intel 852GM GMCH	Integrated Intel 852GM GMCH
Audio	Realtek AC'97 Codec	Realtek AC'97 Codec	Realtek AC'97 Codec
LAN Controller	Dual LAN	Dual LAN	Dual LAN
I/O Connector	Realtek 8100C 10/100 Base-T RJ-45*2 Serial Port *3 USB Port *4; VGA Port *1 PS/2 Mini DIN Keyboard & Mouse Port Audio Line in/out and Mic in Jacks	Realtek 8100C 10/100 Base-T RJ-45*2 Serial Port *3 USB Port *4; VGA Port *1 PS/2 Mini DIN Keyboard & Mouse Port Audio Line in/out and Mic in Jacks	Realtek 8100C 10/100 Base-T RJ-45*2 Serial Port *3 USB Port *4; VGA Port *1 PS/2 Mini DIN Keyboard & Mouse Port Audio Line in/out and Mic in Jacks
Display			
Size	12" TFT LCD Screen	15" TFT LCD Screen	17" TFT LCD Screen
Contrast Ratio	400 : 1	450 : 1	450 : 1
Brightness	250cd/m ²	250cd/m ²	250cd/m ²
Resolution	1024 * 768	1024 * 768	1280 * 1024
Mechanical			
Touch	Taiwan 5-wire Resistive Touch or ELO by option	Taiwan 5-wire Resistive Touch or ELO by option	Taiwan 5-wire Resistive Touch or ELO by option
Device	2.5" IDE HDD * 1, default 40GB	2.5" IDE HDD * 1, default 40GB	2.5" IDE HDD * 1, default 40GB
Power Supply	60W ATX Power Supply	60W ATX Power Supply	60W ATX Power Supply
Bezel	Stainless(Optional Black Plastic Bezel)	Stainless(Optional Black Plastic Bezel)	Stainless(Optional Black Plastic Bezel)
Dimension	252(H)*326(W)*80mm(D)	280(H)*380(W)*82mm(D)	327(H)*416(W)*92mm(D)
Option Ordering	PT-150PH/170PH C2D solution with fan		



Built-in Speaker



IP54 compliant



Compact design



Option Industrial MDM

PT-150PH/PT-170PH
 >> Intel945GM C2D CPU

PT-150PF-DC
 >> 9-36V DC-in

[MOQ]

PT-150PF-400nits
 >> 400nits LCD panel

[MOQ]