

CSB100-520

Fanless



Features

- Supports AMD Geode™ LX processors (LX700, LX800 or LX900)
- Slim box fanless design for a wide variety of applications
- 1x 10/100BaseT RJ-45 port
- Available in black coating color
- One 2.5" HDD drive bay
- Wall mount kit included

Specifications

System Mainboard	IB520F-R
CPU Type	AMD Geode™ LX800
System Speed	500MHz
Memory	1x DDR SO-DIMM, Max. 1GB
Construction	SECC
Chassis Color	Black
Front Panel External I/O	Front audio
Rear Panel External I/O	1x USB port, VGA connector, KB/MS connector, 1x COM port, 1x RJ-45 connector, DC-in jack, 1x PCMCIA socket
Storage	1x 2.5" HDD drive bay
Power Supply	60W power adaptor
Mounting	Desktop or wall mount
Dimensions	172.4mm(W) x113.6mm(D) x 47.4mm(H)

Environmental

Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

CSB100-520FC	Steel Chassis for IB520F-R 3.5" SBC, 2.5" HDD holder, 60W power adaptor
CSB100-520FM	Steel Chassis with IB520F-R 3.5" SBC, 2.5" HDD holder, 60W power adaptor



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.