ANI200-970 Slim Type System for IBASE MI970VF Mini-ITX Motherboard

Fanless System







Specifications

Motherboard

CPU Modul

6

Embedded Systems

RISC SRC

CPU Card

PC 104 Plus

| opeomodiene | |
|-----------------------------|---|
| System Mainboard | MI970VF |
| СРИ Туре | 3rd Generation Intel® Core™ i series mobile CPU, rPGA988B |
| System Speed | Up to 2.8GHz |
| Memory | 2x DDR3 SO-DIMM, 8GB (w/ heatsink) |
| Construction | Aluminum |
| Chassis Color | Silver |
| Front Panel External I/O | Power LED, HDD LED, Power button, Reset button, 2x USB Ports (2.0/3.0) |
| Rear Panel External I/O | 2x COM 1x DVI-1+DVI-D, DisplayPort + dual USB(3.0), 2x dual USB(2.0)+RJ45 1x Audio port (3-port) DC-in jack |
| Storage | 1x 2.5" storage device (SATA II or SATAIII interface), 100GB industrial-grade HDD |
| Power Supply | 120W power adaptor |
| Mounting | Desktop or wall mount (wall mount kit included) |
| Dimensions | 199mm(W) x 232mm(D) x 63.4mm(H) |
| Operating Temperature | 0°C∼ 45°C (32°F∼113°F) |
| Storage Temperature | -20° ~ 80°C (-4°F~176°F) |
| Relative Humidity | 5~90% @ 45°C, (non-condensing) |
| Vibration | SSD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation |
| Others | Digital I/O (4 in/4 out), 2x Realtek 8111E-VL GbE controller |

Features

- Supports 3rd Generation Intel[®] Core[™] i mobile processors
- iSMART for EuP/ErP power saving, auto-scheduler and power resume
- One 2.5" storage device inside
- Available in silver color
- Fanless operation
- Wall mount kit included
- iAMT 8.0

Ordering Information

| | Aluminum System with MI970VF, 3rd Generation Intel® |
|------------|---|
| AMI200-970 | Core™ i series, 8GB DDR3 SO-DIMM, 2.5" 100GB |
| | industrial-grade HDD, 120W power adaptor |

Dimensions

