

IOPS-66

Mid-Range, Open Pluggable Specification Signage Player
with 3rd Generation Intel® Core™ i Processor

Digital Signage Players



Features

- Supports 2nd/3rd Generation Intel® Core™ i7/i5/i3 Mobile Processors
- Intel® HD Graphics 2000/3000 in i3/i5/i7 CPU
- Supports 2x DDR3 1600MHz SO-DIMM memory Max. 16GB
- Expresscard slot and dual mPCIe(x1) slots
- Two RS232 serial ports
- Slim and compact design

Specifications

System Mainboard	IOPS-66 MB
CPU Type	3rd Generation Intel® Core™ i7/i5/i3/ Celeron® Quad-Core/ Dual-Core Mobile Processors
CPU Package	FCBGA1023
Chipset	Intel® QM77 PCH
Memory	1x DDR3 1600MHz SO-DIMM, Max. 8GB (Non-ECC)
Graphics	Intel® HD graphics supports: OpenGL 3.0 DirectX® 11 OpenCL 1.1 MFX Hardware Video Decoder – MPEG-2, AVC, VC-1, JPEG
LAN	1x Intel® 82579 Gigabit LAN controller
Expansion Slots	1x Mini PCI-E(x1)
I/O Interface	1x HDMI 2x USB 3.0 ports 1x RJ45 for LAN 2x Microjack Audio connectors for Line-in / Line-out Power On/Reset button
Auto Control and Monitoring	256 segments, 0, 1, 2...255 (sec/min)
Power Requirement	12~24V (via OPS inter connection)
Construction	Aluminum + SGCC (steel)
Weight	0.9kg (1.98lbs)
Chassis Color	Black
Storage	1x External removable 2.5" HDD drive bay/ SSD drive bay
Power Supply	N/A
Mounting	Open Pluggable Specification
Dimensions	200mm(W) x 119mm(D) x 30mm(H) 7.87"(W) x 4.69"(D) x 1.18"(H)
Operating Temperature	0°C~ 40°C (32°F~104°F)
Storage Temperature	-20° ~ 80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	SSD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation
Certification	CE, FCC

Ordering Information

iOPS-66	OPS System with Intel® Core™ i5 Mobile Processor, 4GB RAM, 250GB HDD
iOPS-66M	OPS System with Intel® Core™ i5 Mobile Processor, without RAM, HDD.

Dimensions

