

RSB200-892

Wide Temp Rugged System for IBASE IB892
3.5" Disk-Size SBC

SBC System

RSB200-884T

Wide Temp Rugged System for IBASE IB884T
3.5" Disk-Size SBC

SBC System



Features

- Fanless System for IBASE IB892 3.5" SBC
- Onboard Intel® Atom™ Processor E660T, 1.3GHz
- Available in silver color
- One 2.5" HDD or SSD
- Internal CFast socket
- Front panel I/O for USB, VGA, COM, LAN and DC-in connector
- DIN-rail mounting

Specifications

System Mainboard	IB892-13T-ASB
CPU Type	Intel® Atom™ Processor E660T
System Speed	1.3GHz
Memory	DDR2-800 1GB onboard
Construction	Steel + Aluminum
Chassis Color	Silver
Front Panel External I/O	1x VGA, 1x COM, 2x USB ports, 1x RJ45, Phoenix connector, On/Off button, Reset button, power LED, HDD LED
Rear Panel External I/O	N/A
Storage	1x 2.5" HDD or SSD 1x MicroSD 1x CFast
Power Supply	Optional 60W DC power supply (Commercial grade only)
Mounting	DIN rail
Dimensions	187mm(W) x 126mm(D) x 53mm(H)
Operating Temperature	-30°C ~ 70°C (-22°F ~ 158°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~95% @ 45°C, (non-condensing)
Vibration	TBC

Ordering Information

RSB200-892	Fanless System with IBASE IB892-13T-ASB 3.5" SBC, w/ Intel® Atom™ E660T(1.3GHz) CPU, 1GB DDR2-800 memory, 2.5" 100GB industrial-grade HDD, DIN rail mounting brackets
------------	---

Features

- Fanless System for IBASE IB884T 3.5" SBC
- Onboard Intel® Atom™ Processor Z510PT, 1.1GHz
- Available in silver color
- One 2.5" HDD or SSD
- Internal Compact Flash socket
- Front panel I/O for USB, VGA, COM, LAN and DC-in connector
- DIN-rail mounting

Specifications

System Mainboard	IB884T-11
CPU Type	Intel® Atom™ Processor Z510PT
System Speed	1.1GHz
Memory	1x DDR2 SO-DIMM, 1GB
Construction	Steel + Aluminum
Chassis Color	Silver
Front Panel External I/O	1x VGA, 1x COM, 2x USB ports, 1x RJ45, DC-in connectors
Rear Panel External I/O	N/A
Storage	1x 2.5" HDD or SSD 1x Compact Flash Disk
Power Supply	Optional 60W DC power supply (Commercial grade only)
Mounting	DIN rail
Dimensions	187mm(W) x 126mm(D) x 53mm(H)
Operating Temperature	-30°C ~ 70°C (-22°F ~ 158°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	TBC

Ordering Information

RSB200-884T-11-HD	Fanless System with IBASE IB884T-11 3.5" SBC, w/ Intel® Atom™ Z510PT(1.1GHz) CPU, 1GB DDR2 SO-DIMM, 2.5" 100GB industrial-grade HDD, DIN rail mounting brackets
-------------------	---

01 Motherboards

02 Disk-Size SBCs

03 CPU Modules

04 PC 104 Plus

05 CPU Cards

06 RISC SBCs

07 Embedded Systems