



Digital Signage Players



Features

- iSMART - for Auto-scheduler and power resume
- Supports 3rd Generation Intel® Core™ i7/i5/i3/ Celeron® QC/DC Processors
- 2x DDR3 SO-DIMM, Max. 16GB
- Intel® HD Graphics Engine
- iAMT Compliance for remote management
- 2x USB 3.0 ports
- 1x Mini PCI-E(x1) expansion slots for wifi, 3G and TV tuner function expansion
- Watchdog timer, Digital I/O, TPM 1.2
- Segregated flow ventilation design

Specifications

| | |
|-----------------------------|---|
| System Mainboard | IB902A |
| CPU Type | 2nd/3rd Generation Intel® Mobile Core™ i7/i5/i3/ Celeron® QC/ DC processors (TDP <= 35W) |
| CPU Socket | rPGA988B |
| Chipset | Intel® QM77 PCH |
| Memory | 2x DDR3 1066/1333/1600 MHz SO-DIMM, Max. 16GB (Non-ECC) |
| Graphics | Intel® HD Graphics supports: OpenGL 3.0 DirectX® 11 OpenCL 1.1 MFX Hardware Video Decoder – MPEG-2, AVC, VC-1, JPEG |
| LAN | 1x Intel® 82579LM Gigabit LAN controller w/ iAMT 9.0 |
| Expansion Slots | Mini PCI-E |
| I/O Interface | 1x HDMI, 1 X DVI-I 1x Microjack Audio connectors for Line-out 1x Gigabit LAN 2x USB 3.0, 1 X RS-232 (RJ45 connector) 1x Power Button with LED light 1x DC Jack |
| Auto Control and Monitoring | Watchdog Timer: 256 segments, 0, 1, 2...255 (sec/ min) |
| Power Requirement | +12V DC-in |
| Construction | SGCC |
| Weight | TBD |
| Chassis Color | Black & White |
| Storage | 1x mSATA 1x SATA 3.0 2.5" HDD Dock |
| Power Supply | 60W power adaptor |
| Mounting | STD system bracket |
| Dimensions | 178mm(W) x 150mm(D) x 35mm(H) |
| Operating Temperature | 0°C ~ 45°C (32°F ~ 113°F) |
| Storage Temperature | -20° ~ 80°C (-4°F ~ 176°F) |
| Relative Humidity | 5~90% @ 45°C, (non-condensing) |
| Vibration | mSATA: 5 grms / 5~500Hz / random operation |
| Certification | CE, FCC |

Ordering Information

| | |
|--------|--|
| SI-62 | Signage Player with Intel® Core™ i5-3610ME processor (3M Cache, up to 3.30 GHz) 4 GB DDR3 SO-DIMM Memory, 2.5" 320GB SATA HDD, 60W power adaptor |
| SI-62M | Signage Player without CPU, RAM, HDD, with 60W Adaptor |
| SI-MK3 | Mounting bracket for SI-24/28/38/62 series |

Dimensions

