

# SM-119P

## 19" SXGA 5:4 High-Brightness Modular Touch Monitor



### Applications

- Outdoor Digital Signage
- Outdoor Self-Service Kiosk
- Smart Agriculture
- Railway Signal and Control
- HMI Solution

### Features

- Patented Display Conversion Device (DCD) Technology
- Designed with Aluminum Die-casting Ultra-Thin Front Frame
- IP65 True Front Panel for Waterproof and Dustproof
- Projected Capacitive Touchscreen
- 1280 x 1024 Resolution and 1600nits Brightness
- Connectors for Display On/Off and External OSD Control
- -10°C to 60°C Operating Temperature



### Ordering Information

Part No.	Description
SM-119P	19" 5:4 SXGA (1280x1024), 1600nits, PCAP Touchscreen


### Packing List

Description
1 x SM-119P
Panel Mount Kits

### Specifications

Model	SM-119P	
Display	Panel Size	19"
	Panel Type	LCD Panel
	Aspect Ratio	5:4
	Resolution	1280 x 1024 (SXGA)
	Viewing Angle	170(H) x 160(V)
	Brightness	1600cd/m <sup>2</sup>
	Contrast Ratio	1000:1
	Color Support	16.7M
Touchscreen	Touchscreen Type	Projected Capacitive (PCAP)
	Surface Hardness	7Mohs
	Transparency	90% (±3%)
System	OSD Control	Touch Monitor On/Off, Auto, Menu, Up and Down, Multi-language OSD
	Speaker	N/A
Environment	Operating Temperature	-10°C to 60°C
	Storage Temperature	-20°C to 70°C
	Humidity	10%~80% (non-condensing)
	Vibration	1.5Grms, 5-500Hz, 3Axis
	Shock	20Grms, Half-sine 11ms
General	Certification	CE / FCC
	Ingress Protection	IP 65 Compliant Front Panel
	Material	Front Panel Construction: Die-cast Flat Surface
	Mounting	Panel Mounting
	Dimensions (W x H x D)	449.7 x 374.7 x 31mm
	Net Weight	5.85kg

## Dimensions



## Viewing

IP65 True Front Panel for Waterproof and Dustproof

High-Brightness up to 1600nits

Aluminum Die-casting Ultra-Thin Front Frame

PCAP Touchscreen

Connectors for Display On/Off and External OSD Control

