

Model Show FW1018SPV1	Specification		
	Description	10.1" IPS 3G-SDI Camera-Top Field Monitor	
	Model	FW1018SPV1	
	Screen Size	10.1"	
	Resolution	1920*1200 pixels	
	Dot pitch	0.1695(H)x0.1695(V)mm	
	Aspect ratio	16:10	
	Brightness	320cd/m ²	
	Contrast	800:1	
	Backlight	LED	
Response Time	25ms		
Viewing Angle	89°/89°(L/R) 89°/89°(U/D)		
Inputs	3G/HD/SD-SDI, HDMI, Ypbpr, Video, Audio(L/R)		
Outputs	3G/HD/SD-SDI, HDMI, Ypbpr, Video		
Audio	Speaker and Stereo Headphone output		
SDI Support Format	480i/ 576i		
	720p (60/59.94/50/30/29/25/24/23.98)		
	1080i (60/59.94/50)		
HDMI Support Format	1080p (60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)		
	480i/ 576i/ 480p/ 576p		
	1080i (60/59.94/50)		
Power Consumption	DC6V-36V		
Input Voltage	≤12W		
Power Connector	DC/ 4-pin XLR		
Battery Plate	F970 (Standard); D28S, LP-E6, V-Mount, Anton Bauer (Optional)		
working Temperature	-20~55℃		
storage Temperature	-30~65℃		
Install Way	1/4"-20 Thread Socket (3 sides left&right&bottom)		
Unit Size	258L×192H×39D (mm)		
Unit Weight	810g		
Advanced Features			
*Focus Assist(1.Red highlight over parts of the image in focus, 2.Red highlight over parts of the monochrome image in focus)			
*Brightness Histogram			
*Exposure(Zebra)			
*False Colors			
*Check Field (Mono/Red/Green/Blue)			
*Centre Marker			
*Screen Marker(80%,85%,90%,93%,96%,2.35:1)			
*Camera 5D II Mode			
*Image Freeze			
*Image Flip (H, V, H/V)			
*Pixel-to-Pixel Mode			
*Zoom All			
*U/D & L/R Zoom			
*4:3&16:9 image adjustable			
*Tally Indicator			
Standard Accessories	Optional Accessories	Packing Details	
Sun Shade	Power Adapter	Box size	31x26.5x9CM
F970 Battery Plate	V Mount Plate	Per box G.W.	1.68kgs
Hot Shoe Mount	D28S Plate	Per Carton	5pcs
Mini HDMI Cable	Anton Plate	Carton Size	48X32X32CM
Tally Kit	LP-E6 Plate	N.W.	8.4kgs/carton
10 inch U bracket	BNC Cable	G.W.	9.05kgs/carton
Operation Manual			