







Model Show T51	Specification			
	Description	Triple 5" 2RU 800×480 Broadcast LCD Rack Mount Monitor with 3G-SDI,HDMI AV input and output		
	Model	T51		
	Screen size	5"×3		
	Resolution	800×480 pixels		
	Dot pitch	0.045(W)×0.135(H) mm		
	Aspect Ratio	16:9		
	Brightness	500cd/m ²		
	Contrast	500:1		
	Backlight	LED		
	Response time	10 ms		
	Viewing Angle	70°/70°(L/R) 50°/70°(U/D)		
	Inputs	HDMI,3G/HD/SD-SDI,Audio(L/R),Video		
	Outputs	HDMI,3G/HD/SD-SDI,Video,3.5mm Audio Jack		
		SDI Support Format	480i/576i	
			720p(60/59.94/50/30/29/25/24/23.98)	
		1080i(60/59.94/50)		
		1080p(60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)		
HDMI Support Format		480i/576i/480p/576p		
		1080i (60/59.94/50)		
		720p (60/59.94/50/30/29/25/24/23.98)		
		1080p(60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)		
Power Consumption		≤25W		
Input Voltage		DC 9V~24V		
	Operating Temperature	- 20℃ ~ 55℃		
	Storage Temperature	- 30℃ ~ 65℃		
	Install Way	Rack Mount		
	Unit Size	482.6Lx88Hx34D mm		
	Unit Weight	1570g		
		Advanced Features		
		1.Wide view angle, High resolution 800 x 400, bright, colorful display		
		2.Slim design and 2RU size		
		3.HDMI,3G/HD/SD-SDI input and loop-through		
		4.Special Features:		
Peaking Focus Assist(Red highlight over parts of the monochrome image in focus)				
Pixel to Pixel				
Centre Marker				
Screen Marker(80%,85%,90%,93%,96%,2.35:1)				
Image Flip (H, V, H/V)				
Check Field(Red,Green,Blue,Mono)				
Image Freeze				
Zoom All				
U/D & L/R Zoom				
5.Monitoring via front panel 3.5mm stereo headphone jacks				
6.Built-in LED tally indicators (Red, Green, Yellow)				
7.Power using included 12-volt supply or use standard 4-pin XLR				
Standard Accessory	Optional Accessory	Packing Details		
3A Power Adapter		Box size	53.2x15.8x10.5CM	
Tally Kit		Per box G.W.	3kg	
Operation Manual		Per Carton		
		Carton Size		
		N.W.		
		G.W.		