



| Model No.: ZO500 | | Specification | | |
|--|---|---|---------------------------|---------------------------------------|
|  <p>Dual HDMI interfaces</p>  | Description | Shimbol ZO500 500FT HDMI Wireless Video Transmission System | | |
| | | Transmitter | Receiver | |
| | Screen | OLED | | |
| | Interface | 1 * HDMI input | | 2 * HDMI output |
| | | 1* HDMI output | | |
| | | DC power input | | DC power input |
| | | 3.5mm headphone jack | | 3.5mm headphone jack |
| | Power Supply Way/Voltage | Type-C | | Type-C |
| | | F970 battery | | F970 battery |
| | Power Consumption | Type-C: 5V/2A | | Type-C: 5V/2A |
| | | <3W | | <2.5W |
| | HDMI Format | 720P@50.60HZ | | 720P@50.60HZ |
| | | 1080I@50.60HZ | | 1080I@50.60HZ |
| | | 1080P@24/25/30/50/60HZ | | 1080P@24/25/30/50/60HZ |
| | | HDMI Type A | | HDMI Type A |
| | Frequency | 5.1-5.8GHz | | 5.1-5.8GHz |
| | Modulation Mode | OFDM | | OFDM |
| | Transmission Power/Receiving Sensitivity | Maximum 17dBm | | -87dBm |
| | Band Width | 20MHZ | | 20MHZ |
| | Occupied Bandwidth | 20/40MHZ | | 20/40MHZ |
| | Latency | Min 0.08S | | Min 0.08S |
| | Operating Temperature | 0°C ~ 40°C | | 0°C ~ 40°C |
| | Storage Temperature | -20°C ~ 60°C | | -20°C ~ 60°C |
| | Unit Size(mm) | 63.5L*15W*103H | | 63.5L*15W*103H |
| | Unit Weight | 120g | | 120g |
| | | Standard Accessory | Optional Accessory | Packing Details |
| | | 1× Transmitter | | Box Size: 131 * 97.5 * 81.5 mm |
| | | 1× Receiver | | Per box G.W.: 510g |
| | 1× User Manual | | Per Carton: 20sets | |
| | 1×Type C cable | | Carton Size: | |
| | | | G.W. | |
| | | | | |