






Shenzhen ZO Video Technology Co., Ltd

Contact : COCO Ma ; Tel : + 86 13265586527 ;
 Email : coco@zeroone-video.com ; Website : www.zeroone-video.com
 Add: 2C, 2nd Floor, Building 6, Longbi Industrial Park No.27 Dafa Road, Bantian Street, Longgang District, Shenzhen, Guangdong,China

Model No.: ZO600MS	Specification		
  	Description	Shimbol ZO600MS Dual-Band 1000FT 5.5 inch Touchscreen 3D Lut HDMI 3G-SDI Wireless recording Monitor	
	Monitor	Screen	5.5" Touch Panel
		Resolution	1920*1080
		Contrast Ratio	1200:1
		Brightness	2000cd/m2
	Interface	1* HDMI input 1* SDI input	
		1* HDMI output 1* SDI output (Note: When the monitor act as a TX, the SDI output does not work)	
		DC power input	
		3.5mm headphone jack	
		SD Card slot	
		F970 battery	
		DC Input	
	Power Supply Way/Voltage	DC6.5V-16.8V	
	Voltage	DC6.5V-16.8V	
	Power Consumption	<13W	
	Video Input Format	1920*1080p60/59.94/50/30/29.97/25/24/23.98 1920*1080i60/59.94/50 1280*720p60/59.94/50	
	Video Recording Format	MP4(A single file can't exceed 4G)	
	LUT Format	Cube(17*17*17/33*33*33)	
	Transmission Frequency Band	2.4G&5G	
	Modulation Mode	OFDM	
	Transmission Power/Receiving Sensitivity	Maximum 17dBm	
	Band Width	20MHZ	
	Audio Frequency	48KHZ	
	Occupied Bandwidth	20/40MHz	
	Latency	Min 0.08S	
	Operating Temperature	0°C ~ 40°C	
	Storage Temperature	-20°C ~ 60°C	
	Unit Size(mm)	151*103*29.5	
	Unit Weight	340g	
	Advanced Features		
*Scope Menu (Waveform、RGB-Paral、Histogram、Vector; Adjustable transparency)	*Recording (User、Trigger、TimeCode) : Support recording file name customization		
*Safe Frames (80%、85%、90%、93%、96%) , support color, line width selection	*Playback(Built-in player, optional files, free drag and drop playback time)		
*Grip (Lines 2 3 4)	*Support brightness, contrast, chromaticity and other display functions adjustment		
*Ratio Marker(Support color, line width selection, support ratio customization)	*Embedded Audio		
*Aspect Ratio (0、50%、100%)	*Support HDR (PQ、HLG) Monitoring		
*Center Marker	*RGB Adjustment (RGB Gain, RGB Offset)		
*Focus Assist (Red, Green, Blue, Grey four colors optional;0-100 focus sensitivity adjustable)	*Color Temperature Adjustment (User、5600K、6500K)		
*ZOOM (100%-400%) , Double touch zoom, zoom free dragging	*Scan Mode (Noman, Under Scan)		
*Zebra Exposure (1-100IRE adjustable)	*Backlight adjustment (120-2000nits)		
*False Colors	*Fan mode (Auto、Off、Low、High)		
*Check Field (Red, Green, Blue, Grey)	*SD Card Formatting Function		
*3D-LUT (Presets and customization, support for user-defined 3D LUT uploads)	*SD formatting (32-256G supported)		
*Wireless frequency switching, wireless group connection	*Function shortcut(F1,F2)		
*1 TX to 2 RX +APP Mode			
*Gamma curve selection	*External sunshade available		
Standard Accessory	Optional Accessory	Packing Details	
1× Wireless Monitor		Box Size:	
1× SD Card		Per box G.W.:	
1× Tempered Screen Protector		Per Carton:	
1× HDMI Cable		Carton Size:	
1× SDI Cable		G.W.	
5× Antennas			
1× Hot Shoe Mount			
1× User Manual			