# **VBOX-3620-M12X**

# Intel Gen6 Core i7-6600U CPU with Isolated Input 3 x GbE and 1 x iAMT In-Vehicle Computer







**Battery Backup** 

#### Taiwan Patent No. M447854 Taiwan Patent No. M448011

#### System

| CPU         | Intel Gen6 Core i7-6600U 2.6GHz up to 3.4GHz |
|-------------|--|
|             | Intel Gen6 Core i5-6300U 2.4GHz up to 3GHz   |
|             | Intel Gen6 Core i3-6100U 2.3GHz              |
|             | Intel Gen 6 Dual Core 3955U 2.0GHz           |
| Memory      | 2 x SO-DIMM DDR4 up to 32GB                  |
| LAN Chipset | 2 x Intel I210AT and 1 x Intel i219LM        |
| Audio       | Realtek ALC662 HD Codec Onboard              |
| Watchdog    | Watchdog Timer Support, Offer 1 – 255 Step   |

#### **I/O**

| Serial Port     | 4 x RS-232/422/485, w/ isolation (Auto Direction Control) |
|-----------------|---|
| USB Port        | 2 x USB 3.0 Ports, 2 x USB 2.0 Ports                      |
| LAN             | 3 x 10/100/1000 Mb/s w/ M12 x-code (1 port with iAMT)     |
| Video Port      | 2 x DP Port, 1 x VGA (Support Triple Independent Display) |
| DIO Port        | 8 x GPI and 4 x GPO w/ isolation                          |
| Audio           | 1 x Line-out and 1 x Mic-in (Line-in Optional)            |
| SIM Card Socket | 2 x SIM Card Sockets, supported onboard with eject        |
|                 | 6 x SIM Card Sockets (Optional)                           |
| Expansion Bus   | 3 x Mini-card slots                                       |
|                 | 1 x M.2 slot  |

### Graphics

| Graphics   | Intel® HD Graphics 520                                   |
|------------|--|
|            | DirectX Video Acceleration (DXVA) for Accelerating Video |
|            | Processing - Full AVC/VC1/MPEG2 HW Decode                |
|            | Supports DirectX 11/10.1/10/9 and OpenGL 4.0             |
| Resolution | Up to 4096 x 2304@60 Hz                                  |

## Storage

| •    |  |
|------|--|
| Туре | 2 x 2.5" Drive Bay for SATA Type HDD/SSD, RAID 0, 1, 5 |
|      | 1 x SATA DOM   |

# Features

- Intel Core i7-6600U / i5-6300U / i3-6100U
- Wireless support LTE, 3.5G w/ SIM Card, WLAN GPS Dead Reckoning, GSM/GPRS, BT
- 3 x GbE including 1 with iAMT
- Isolated wide Input Range 9-36VDC
- Smarter Vehicle Power Ignition for Variety Vehicle
- Dual Hot Swappable SATA Storage, RAID 0,1,5
- EN50155 Tx

#### **Power Requirement**

| Power Input   | 9V - 36V DC Power Input with Isolation                |
|---|---|
| Power Protection  | Automatics Recovery Short Circuit Protection          |
| Power Management Vehicle Power Ignition for Variety Vehicle |   |
| Power Off Control   | Power off Delay Time Setting by Software and BIOS     |
| Battery (UPS)*  | Internal Battery Kit for 10 Mins Operating (Optional) |
|   | Patent No. : M447854 - Build-in Battery               |

 $\star$  with 6 x SIM card slots option cannot have Battery option

#### Environmental

| Operating Temp.   | -40°C ~ 70°C   |
|---|--|
| Storage Temp.   | -40°C ~ 80°C   |
| Relative Humidity   | 0% RH – 95% RH   |
| Vibration(random)   | IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD |
| Vibration Operating MIL-STD-810G, Method 514.6, Procedure I, Category 4 |  |
| Shock   | Operating: MIL-STD-810G, Method 516.6, Procedure I,    |
|   | Trucks and semi-trailers=15G (11ms) with SSD           |
| Certifications  | CE, FCC Class A, EN50155, EN50121                      |
|   |  |

### Mechanical

| Construction | Aluminum Alloy                         |
|--------------|--|
| Mounting     | Supports Both of Wall-mount/VESA-mount |
| Weight       | 1900g                                  |
| Dimensions   | 250 x 150 x 55 mm                      |

### **Ordering Information**

| Part Number | VBOX-3620-M12X-000                               |
|-------------|--|
| Description | Intel Gen6 Core i7-6600U CPU with Isolated Input |
|             | 3x GbE with 1 x iAMT In-Vehicle Computer         |