



# MPC25/L

**Most economical, smallest multimedia computer**

The MICROSPACE® MPC25 computer system contains the MSB200 board and its interfaces, based on Intel's Atom processor with up to 1.6GHz. It boots from CompactFlash, LAN, USB, SSD or from the optionally integrated 2.5" hard disk. The MPC25 is 27mm in height and is the smallest computer of its kind. The PCIe-MiniCard makes it possible to integrate WLAN or field buses. Power is supplied directly with 12V or with a 110/220V power supply unit.

## Applications

- \_ Cost-effective information terminals (LAN, 3D-VGA)
- \_ Multimedia system
- \_ Computer with very low power consumption
- \_ 3D video (DiV-X, DVD) player

## Ordering information

Item	No.	Description
HD250GB	807466	250GB hard drive SATA 0°C to +50°C operating temperature
WLAN	812048	Optional WLAN (PCIe MiniCard)

Technical data	MPC25-2GB	MPC25-1GB	MPC25L-05GB
<b>CPU</b>	Intel® Atom Z530	Intel® Atom Z530	Intel® Atom Z510
<b>ISA-BUS</b>	-	-	-
<b>PCI-BUS</b>	-	-	-
<b>PCI Express-BUS</b>	PCIexpress MiniCard	PCIexpress MiniCard	PCIexpress MiniCard
<b>2<sup>nd</sup> Level cache (kB)</b>	512	512	512
<b>Performance (GHz)</b>	1.6	1.6	1.1
<b>DRAM Min-Max (GB)</b>	2	1	0.5
<b>CompactFlash socket (Type I/II)</b>	yes, CF 256MB inst.	yes, CF 256MB inst.	yes
<b>Keyboard, mouse (PS/2)</b>	-	-	-
<b>Boot drive</b>	CF, USB, LAN, Opt. HD	CF, USB, LAN, Opt. HD	CF, USB, LAN, Opt. HD
<b>IDE interface S-SATA</b>	yes	yes	yes
<b>Digital in</b>	-	-	-
<b>Digital out</b>	-	-	-
<b>COM1</b>	-	-	-
<b>COM2</b>	-	-	-
<b>COM3</b>	-	-	-
<b>COM4</b>	-	-	-
<b>LPT1</b>	-	-	-
<b>USB (2.0)</b>	6x (1x internal)	6x (1x internal)	6x (1x internal)
<b>CAN1-V2.0</b>	-	-	-
<b>CAN2-V2.0</b>	-	-	-
<b>LAN Port A</b>	1GB-LAN (PCIe)	1GB-LAN (PCIe)	1GB-LAN (PCIe)
<b>LAN Port B</b>	100MB-LAN	100MB-LAN	-
<b>Audio</b>	Stereo In/Out	Stereo In/Out	Stereo In/Out
<b>Video controller</b>	Intel®	Intel®	Intel®
<b>Video memory (MB)</b>	128	128	128
<b>LCD interface</b>	-	-	-
<b>DVI interface</b>	yes	yes	yes
<b>CRT interface</b>	-	-	-
<b>Video input</b>	-	-	-
<b>Watchdog</b>	yes	yes	yes
<b>Power normal</b>	10V-20V/6W	10V-20V/5W	10V-20V/5W
<b>Power suspend</b>	0.1W	0.1W	0.1W
<b>Power management</b>	yes	yes	yes
<b>RTC battery onboard</b>	400mAh (>10 years)	400mAh (>10 years)	400mAh (>10 years)
<b>Cooling type</b>	passive	passive	passive
<b>Operating temperature (without hard disk)</b>	-25°C to +70°C	-25°C to +70°C	-25°C to +70°C
<b>Extended operating temperature</b>	-	-	-
<b>Size (W x L x H in mm)</b>	165 x 110 x 27	165 x 110 x 27	165 x 110 x 27
<b>Weight</b>	500 g	500 g	500 g
<b>MTBF</b>	>100'000h (without HD)	>100'000h (without HD)	>100'000h (without HD)
<b>Special features 1</b>	-	-	-
<b>Special features 2</b>	-	-	-
<b>Special features 3</b>	FreeDOS + Linux inst.	FreeDOS + Linux inst.	-
<b>Part no.</b>	812082	812081	812070

Manufacturer:

**DIGITAL-LOGIC**  
 smart embedded computers

 DIGITAL-LOGIC | Nordstrasse 11/F | CH-4542 | Luterbach / Switzerland  
 Phone +41 (0)32 681 58 00 | Fax +41 (0)32 681 58 01  
 sales@digitallogic.com | www.digitallogic.com

Distribution: